

## CR 105 – CR115 Amplified Paging Receiver Units

*DTMF or CTCSS controlled*

(150-174 MHz & 440-470 MHz)

### General Specifications:

- Excellent sound quality,
- No interferences and noises,
- Unlimited expanding groups,
- 75 Watt RMS sound power,
- 4 speakers can be connected,
- Microprocessor controlled,
- Waterproof IP65 Fiber Box Case
- Designed and Produced by TEKSER

### Technical Specifications:

- Operating Frequencies: 150.000 - 174.000 MHz
- Oscillator Type: PLL sensitized,
- Channel Space: 25 KHz,
- Modulation Type: FM (+/- 7KHz /3db)
- Receiver Sensitivity: 0,16 uV / 12 db SINAD
- Operating Temperature: -10 +60 C
- Operating Voltage: 220-240 VAC
- Current on Standby: 45 mA,
- Amplificatory Power: 75 Watt RMS/4 ohm
- Sound Frequency : 30 Hz-3,5 KHz
- DTMF or CTCSS controlled
- Dimensions:(G,Y,D mm): 200x170x300
- Weight: 5,7 Kg



## Wireless Paging Transmitter Unit

*DTMF or CTCSS controlled*

(146-174 MHz & 438-470 MHz)

### Technical Specifications:

- RF Transmitter as Motorola CM Series Mobil Radio,
- Microprocessor controlled, 25 Watts RF Power,
- Gong tone and Siren tones for civil defense (Red, Black, Yellow)
- 99 receiver units control capacity,
- Microphone Input
- Line Input for Music Broadcasting,
- Metallic Chassis,
- Dimensions (G,Y,D mm); 340x295x10
- Designed and Produced by TEKSER

